

Model No.: PMT-20N12AL03-04  
 Product Line: Tymphany

Rev: 1  
 Last Update: 2017-04-25 14:32:09

## Product Description

This 20 mm 4 ohm compact Premium Micro Transducer is designed for computer, television array, and similar applications. It features a neodymium-iron-boron magnet, a light aluminium cone, and a high-temperature polycarbonate frame. The PMT family's transducers feature low resonant frequencies and a full range bandwidth.



## Specifications

|                               |             |        |       |           |                            |      |              |
|-------------------------------|-------------|--------|-------|-----------|----------------------------|------|--------------|
| DC Resistance                 | Revc        | Ohms   | 3.62  | 5.0%      | Energy Bandwidth Product   | EBP  | (1/Qes)*fs   |
| Minimum Impedance             | Zmin        | Ohms   | 4.46  | 7.5%      | Moving Mass                | Mms  | g            |
| Voice Coil Inductance         | Le          | mH     | 0.02  |           | Suspension Compliance      | Cms  | um/N         |
| Resonant Frequency            | Fs          | Hz     | 398.7 | 15%       | Effective Cone diameter    | D    | cm           |
| Mechanical Q Factor           | Qms         |        | 1.89  |           | Effective Piston Area      | Sd   | cm^2         |
| Electrical Q Factor           | Qes         |        | 4.49  |           | Effective Volume           | Vas  | L            |
| Total Q Factor                | Qts         |        | 1.33  |           | Motor Force Factor         | BL   | Tm           |
| Ratio Fs/Qts                  | F           | Fs/Qts | 300   |           | Motor Efficiency Factor    | β    | (T*M^2)/Ohms |
| Half Space Sensitivity @2.83V | db@2.83V/1M | dB     | 76.09 | +/- 1.0db | Voice coil former Material | VCfm | KSV          |
| Half Space Sensitivity @1W/1M | db@1W/1M    | dB     | 73.5  | +/- 1.0db | Voice coil inner diameter  | VCd  | mm           |
| Gap Height                    | Gh          | mm     | 0.8   |           | Rated Noise Power          | P    | W            |
| Maximum Linear Excursion      | Xmax        | mm     | 0.3   |           | Test Spectrum Bandwidth    |      | 400-20K      |
| Ferrofluid Type               | FF          |        |       |           | Driver Size                | Inch | 20 mm        |
| Driver Mass                   | Kg          |        | 0     |           |                            |      |              |

## Frequency and Impedance Response



Highcharts.com